

# NKB1000-E

## Network Keyboard



**Features :**

Keyboard to Control

- Dahua High Speed Dome
- Dahua Standalone DVR
- Network Video Server

Connection

- RS485, RS422 (reserved), USB, RS232 & Network

Functions

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern
- Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS or DSS platform via USB



**Technical Specification**

Model

Model NKB1000-E

General

|  |   |
|--|---|
| Keyboard Key panel   | Electromechanical   |
| Joystick   | 3-axis, vector-solving, with twisting, return to-center head                                      |
| Keyboard Connector   | RJ-45, RS232, RS485, RS422 (reserved), USB  |
| Keyboard Communication   | Direct Mode, Network Mode   |
| Direct Mode  | Interface:<br>1 RS232/2 RS485<br>DVR Protocol: DH-2<br>Dome Protocol: DH-SD1/PELCO-D/PELCO-P, etc |
| Network Mode   | Interface: RJ45<br>DVR/Network Dome:<br>IP Address/Port/Protocol                                  |
| Display  | LCD, 75.2mm×33.85mm   |
| Maximum Number of Users  | 64 (including "admin")  |
| Max RS485 Addresses (Each User)                                    | 256   |
| Max Number of PTZ (IPC) That Can be Added over Network (Each User) | 2048  |

Environmental

|                     |  |
|---------------------|--|
| Power Supply        | Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/2A  |
| Power Consumption   | 5W   |
| Working Temperature | -10C~+55C  |
| Working Humidity    | 10% ~ 90%  |
| Atmosphere Pressure | 86kpa~106kpa   |
| Dimension           | 330mm×139mm×53mm (W×D×H)(height: 103mm including joystick) |
| Weight              | 1.3kg (Including package)                                  |

**Dimensions(mm)**

